

SCHOEN TERMINAL



RING VINYL-INSULATED TERMINAL



TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
RVS 1.25-3.5	Merah, Biru, Kuning, Hitam	0.25 - 1.5
RVS 1.25-4	Merah, Biru, Kuning, Hitam	0.25 - 1.5
RVS 1.25-5	Merah, Biru, Kuning, Hitam	0.25 - 1.5
RVS 1.25-6	Merah, Biru, Kuning, Hitam	0.25 - 1.5
RVS 2-3.5	Merah, Biru, Kuning, Hitam	1.25 - 2.5
RVS 2-4	Merah, Biru, Kuning, Hitam	1.25 - 2.5
RVS 2-5	Merah, Biru, Kuning, Hitam	1.25 - 2.5
RVS 2-6	Merah, Biru, Kuning, Hitam	1.25 - 2.5
RVS 2-8	Merah, Biru, Kuning, Hitam	1.25 - 2.5
RV 3.5-4	Merah, Biru, Kuning, Hitam	2.5 - 4
RV 3.5-5	Merah, Biru, Kuning, Hitam	2.5 - 4
RV 3.5-6	Merah, Biru, Kuning, Hitam	2.5 - 4
RVS 5.5-4	Merah, Biru, Kuning, Hitam	4 - 6
RVS 5.5-5	Merah, Biru, Kuning, Hitam	4 - 6
RVS 5.5-6	Merah, Biru, Kuning, Hitam	4 - 6
RVS 5.5-8	Merah, Biru, Kuning, Hitam	4 - 6

SPADE VINYL-INSULATED TERMINAL



TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
SVS 1.25-3.5	Merah, Biru, Kuning, Hitam	0.25 - 1.5
SVS 1.25-4	Merah, Biru, Kuning, Hitam	0.25 - 1.5
SVS 2-3.5	Merah, Biru, Kuning, Hitam	1.25 - 2.5
SVS 2-4	Merah, Biru, Kuning, Hitam	1.25 - 2.5
SV 3.5-4	Merah, Biru, Kuning, Hitam	2.5 - 4
SV 3.5-5	Merah, Biru, Kuning, Hitam	2.5 - 4
SV 3.5-6	Merah, Biru, Kuning, Hitam	2.5 - 4
SVL 5.5-4	Merah, Biru, Kuning, Hitam	4 - 6
SVL 5.5-5	Merah, Biru, Kuning, Hitam	4 - 6
SVL 5.5-6	Merah, Biru, Kuning, Hitam	4 - 6

## VINYL-INSULATED PIN TERMINAL



TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
PTV 1.25-12	Merah, Kuning, Biru	0.25 - 1.5
PTV 2-12	Merah, Kuning, Biru	1.25 - 2.5
PTV 5.5-13	Merah, Kuning, Biru	4 - 6

## VINYL-INSULATED BLADE TERMINAL



TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
DBV 1.25-18	Merah	0.25 - 1.5
DBV 2-18	Biru	1.25 - 2.5
DBV 5.5-18	Kuning	4 - 6

## VINYL-INSULATED FEMALE DISCONNECTORS



TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
FDD1.25-250	MERAH	0.25 - 1.5
FDD2-250	BIRU	1.25 - 2.5
FDD5.5-250	KUNING	4 - 6

## VINYL-INSULATED MALE DISCONNECTORS




TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
MDD1.25-250	MERAH	0.25 - 1.5
MDD 2-250	BIRU	1.25 - 2.5
MDD 5.5-250	KUNING	4 - 6

## VINYL FULLY INSULATED FEMALE DISCONNECTORS



TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
FDFD 1.25-250	MERAH	0.25 - 1.5
FDFD 2-250	BIRU	1.25 - 2.5
FDFD 5.5-250	KUNING	4 - 6


## VINYL-INSULATED BUTT SPLICE TERMINAL



TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
BV 1.25	MERAH	0.25 - 1.5
BV 2	BIRU	1.25 - 2.5
BV 5.5	KUNING	4 - 6


**VINYL-INSULATED BULLET DISCONNECTORS**


TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
MPD 1.25-156	MERAH	0.25 - 1.5
MPD 2-156	BIRU	1.25 - 2.5
MPD 5.5-195	KUNING	4 - 6


**VINYL-INSULATED RECEPTACLE DISCONNECTORS**

TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
FRD 1.25-156	MERAH	0.25 - 1.5
FRD 2-156	BIRU	1.25 - 2.5
FRD 5.5-195	KUNING	4 - 6


**INSULATED TWIN CORD END TERMINAL**

TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
TE 0508	WHITE	2 X 0.5
TE 7508	BLUE	2 X 0.75
TE 1008	M, B, H, K	2 X 1
TE 1508	BLACK	2 X 1.5
TE 2510	GREY	2 X 2.5
TE 4012	ORANGE	2 X 4
TE 6014	GREEN	2 X 6
TE 1014	BROWN	2 X 10
TE 1614	IVORY	2 X 16



**INSULATED CORD END TERMINAL**

TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
E 0508	WHITE	0.5
E 7508	BLUE	0.75
E 1008	RED	1
E 1508	BLACK	1.5
E 2508	GREY	2.5
E 4010	ORANGE	4
E 6012	GREEN	6
E 1012	BROWN	10
E 1612	IVORY	16
E 2516	BALCK	25
E 3516	BEIGE	35
E 5020	OLIVE	50
E 7025	BLACK	70




### NON-INSULATED CORD END TERMINAL

TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
EN 7508	NON INSULATED	0.75
EN 1008	NON INSULATED	1
EN 1508	NON INSULATED	1.5
EN 2508	NON INSULATED	2.5
EN 4010	NON INSULATED	4
EN 6012	NON INSULATED	6
EN 1012	NON INSULATED	10
EN 1612	NON INSULATED	16
EN 2516	NON INSULATED	25
EN 3516	NON INSULATED	35
EN 5018	NON INSULATED	50
EN 5022	NON INSULATED	50



### RING NON-INSULATED TERMINAL

TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
RNB S1.25-3.5	NON INSULATED	0.25 - 1.5
RNB S1.25-4	NON INSULATED	0.25 - 1.5
RNB S1.25-5	NON INSULATED	0.25 - 1.5
RNB S1.25-6	NON INSULATED	0.25 - 1.5
RNB S2-4	NON INSULATED	1.25 - 2.5
RNB S2-5	NON INSULATED	1.25 - 2.5
RNB S2-6	NON INSULATED	1.25 - 2.5
RNB S2-8	NON INSULATED	1.25 - 2.5
RNB 3.5-4	NON INSULATED	2.5 - 4
RNB 3.5-5.5	NON INSULATED	2.5 - 4
RNB 3.5-6	NON INSULATED	2.5 - 4
RNB S5.5-4	NON INSULATED	4 - 6
RNB S5.5-5	NON INSULATED	4 - 6
RNB S5.5-6	NON INSULATED	4 - 6
RNB S5.5-8	NON INSULATED	4 - 6




### SPADE NON-INSULATED TERMINAL

TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
SNB S1.25-3.5	NON INSULATED	0.25 - 1.5
SNB S1.25-4	NON INSULATED	0.25 - 1.5
SNB S2-3.5	NON INSULATED	1.25 - 2.5
SNB S2-4	NON INSULATED	1.25 - 2.5
SNB 3.5-5.5	NON INSULATED	2.5 - 4
SNB 3.5-6	NON INSULATED	2.5 - 4
SNB S5.5-4	NON INSULATED	4 - 6
SNB S5.5-6	NON INSULATED	4 - 6



## PVC INSULATED TERMINAL SLEEVE

TIPE	SPESIFIKASI		
	WARNA	DIAMETER (mm)	UKURAN KABEL (mm)
V - 1.25	Merah, Kuning, Biru, Hijau Hitam	3.1	2.5
V - 2	Merah, Kuning, Biru, Hijau Hitam	3.7	4
V - 3.5	Merah, Kuning, Biru, Hijau Hitam	4.1	6
V - 5.5	Merah, Kuning, Biru, Hijau Hitam	5.2	10
V - 8	Merah, Kuning, Biru, Hijau Hitam	6.2	16
V - 14	Merah, Kuning, Biru, Hijau Hitam	8	25
V - 22	Merah, Kuning, Biru, Hijau Hitam	9.5	35
V - 38	Merah, Kuning, Biru, Hijau Hitam	11.8	50
V - 60	Merah, Kuning, Biru, Hijau Hitam	13.5	70
V - 70	Merah, Kuning, Biru, Hijau Hitam	15	95
V - 100	Merah, Kuning, Biru, Hijau Hitam	18	120
V - 125	Merah, Kuning, Biru, Hijau Hitam	20	150
V - 150	Merah, Kuning, Biru, Hijau Hitam	22	185
V - 200	Merah, Kuning, Biru, Hijau Hitam	24	240
V - 250	Merah, Kuning, Biru, Hijau Hitam	26,5	300
V - 325	Merah, Kuning, Biru, Hijau Hitam	29	400
V - 400	Merah, Kuning, Biru, Hijau Hitam	36	500
V - 500	Merah, Kuning, Biru, Hijau Hitam	40	630
V - 630	Merah, Kuning, Biru, Hijau Hitam	44	630



## SCREW ON WIRE CONNECTOR

TIPE	SPESIFIKASI	
	WARNA	UKURAN KABEL (mm)
SP 1	GREY	0.5 - 1
SP 2	BLUE	1 - 1.5
SP 3	ORANGE	1.5 - 2.5
SP 4	YELLOW	2.5 - 4

## TERMINAL BLOCK



TIPE	SPESIFIKASI	
	POLE	ARUS
TB-1503	3	15 A
TB-1504	4	15 A
TB-1506	6	15 A
TB-1512	12	15 A
TB-2503	3	25 A
TB-2504	4	25 A
TB-2506	6	25 A
TB-2512	12	25 A

## CABLE TIE

- Cable tie dapat diaplikasikan untuk mengikat kabel, rangkaian kabel otomatis, packaging, kerajinan tangan, pengikat pipa, dll.
- Packing 100 pcs/bag
- Diproduksi dengan material Nylon 66 (UL Recognized), memenuhi standar RoHS serta UL Flammability 94V.2



TIPE	PANJANG
CV 3-100	2.5 x 100
CV 4-150	3.6 x 150
CV 3-200	2.5 x 200
CV 4-200	3.6 x 200
CV 5-200	4.8 x 200
CV 4-250	3.6 x 250
CV 5-250	4.8 x 250
CV 4-300	3.6 x 300
CV 5-300	4.8 x 300
CV 8-300	7.6 x 300
CV 5-400	4.8 x 400
CV 5-450	4.8 x 450
CV 9-550	8.8 x 550

## CURRENT TRANSFORMER



TIPE	SPESIFIKASI			
	DIMENSI (mm)	CLASS	BURDEN	RATING
MSQ - 30	10 x 30	0.5	1.5	50 / 5A
MSQ - 30	10 x 30	0.5	1.5	60 / 5A
MSQ - 30	10 x 30	0.5	1.5	75 / 5A
MSQ - 30	10 x 30	0.5	2.5	100 / 5A
MSQ - 30	10 x 30	0.5	2.5	150 / 5A
MSQ - 30	10 x 30	0.5	2.5	200 / 5A
MSQ - 30	10 x 30	0.5	2.5	250 / 5A
MSQ - 40	10 x 40	0.5	5	300 / 5A
MSQ - 40	10 x 40	0.5	5	400 / 5A
MSQ - 40	10 x 40	0.5	5	500 / 5A
MSQ - 40	10 x 40	0.5	5	600 / 5A

### Marketing Office

Jl. Pangeran Jayakarta No. 141 M  
 Tel. +62 21 2268 5999  
 Fax. +62 21 2268 3803  
 email: pen@pumaelektrik.com  
 web: www.pumaelektrik.com